

SERVICE NOTICE

Subject	A2L Usage
Date	1/1/2020
Product	DC Pumps & DC Recovery Units DC Charging Station
Affected Models	NP2DLM NP4DLM NRP6Di NRP6DV NRP8Di NRP8DV NP12DM NRDD NRDC4M NRC62D

Due to the recent increase in interest within the HVACR industry in lower "GWP" refrigerants, the market for such refrigerants and tools to work with them has increased. These refrigerants tend to fall into safety classification of A2/A2L/A3.

In the US the rise of A2L mildly flammable refrigerants such as R32, R454B, R1234ZE/YF, etc. has necessitated the need for recovery machines and vacuum pumps that can be used with mildly flammable refrigerants.

NAVACs' **NRDD** and **NRDC4M** refrigerant recovery machines and the **NP2DLM**, **NP4DLM**, **NRP6Di**, **NRP8Di NRP6DV**, **NRP8DV**, and **NP12DM** vacuum pumps and the **NRC62D** charging machine are compatible with A2L refrigerant systems.

As with any HVACR system or refrigerants caution should be taken when working around A2L refrigerants. Ensure adequate airflow in your work area and never mix any refrigerants. The purge functions available on the recovery and charging machine, when performed properly, will prevent accidental mixing of refrigerants inside the machines.

For any further clarification or instructions, please contact the NAVAC Technical Support Department at 1-877-MY-NAVAC or

email: techsupport@navacglobal.com