



QVBC.SA45820 - Commercial Refrigeration Recovery/Recycling Equipment Certified for Performance Characteristics in Accordance with the United States Clean Air Act

NAVAC Inc.
1099 Wall St W Ste 179
Lyndhurst, NJ 07071-3624 United States

SA45820

Certified for performance in accordance with EPA's Minimum Requirements for Recycling or Recovery Equipment.

Performance Data

Model Dsg	Refrigerant	Push/Pull Recovery Rate (kg/min)	Liquid Recovery Rate (kg/min)	Vapor Recovery Rate (kg/min)	Final Recovery Vacuum Level kPa	Moisture Content (ppm by weight)	Chloride Ions (ppm by weight)	Acidity (ppm by weight)	High Boiling Residue (% by volume)	Particulates Solids Visual	Non-condensable Purge Loss (<3% by weight)	Refrigerant Loss, Weight %	Residual Trapped Refrigerant kg	High Temp (104 F) Vapor Recovery Rate (kg/Min)
"NRDD", "NRDDF"	R22	7.73	5.04	0.29	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.007	0.34
	R134a	5.81	3.56	0.26	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.006	—
	R407C	7.75	5.56	0.28	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.006	—
	R410A	8.35	6.55	0.34	50.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.005	—

* Product identification, construction variations, ratings and performance data.

iq.ulprospector.com/en/profile?e=4605085