



Empowering you to work smarter

PRO  
SERIES

## NP7DPF

### Vacuum Pump for Flammable Refrigerants



**A2L, A2 & A3\*\***  
**Compatible**



## Reliability • Ignition-Proof

#### Sparkless, Ignition-Proof Design\*

- Designed and tested to UL 121201, CSA C22.2 No. 213-17 and IEC 60079-7 Standards
- Suitable for A2L, A2 and A3 refrigerants\*\*

#### Internal Check Valve

- Prevent oil backflow

#### Dual-Stage Integrated Cylinder Design

- High ultimate vacuum
- High reliability

#### Forced Oil Circulation

- Improved efficiency and durability

#### Lifting Hook

- Safe & convenient for rooftop use

Model		NP7DPF
Power Supply		115V / 60Hz
Flow Rate	CFM	7
Run Load Amps	A	4
Ultimate Vacuum	micron	15
Pump Design		Dual-Stage, AC Motor
Motor Power	HP	3/4
Inlet Port	in	1/4", 3/8", 1/2" Flare
Oil Capacity	oz	15
Dimension	in	14 × 5 × 11.3
Weight	lbs	26

**1-YEAR WARRANTY**

\* For evacuation of sealed HVAC/R systems only. Warranty may void if used for any other purposes.

\*\* PROHIBITED to use with IIB and IIC refrigerants: RE170, R702, R1150, R429A, R432A, R435A, R510A.