



# NRDD Digital DC Recovery Unit

AZL





# **Fastest in Its Class**

### Fastest in Direct Vapor for R410A, R22

• UL verified recovery rate, best performance in its class

### Twin Cylinder with 2-Row Oversized Condenser

Fast recovery

Brushless DC MotorLight and more efficient

#### **Oil-Free Compressor**

• Suitable for all commonly used refrigerants

## Large Backlit Display

- Easy-to-read large LCD display
- Backlit for clarity

#### **Purge Function**

• Prevent mixing of various refrigerants

Technology

| Model   |            | NRDD  |               |               |              |                    |
|---|------------|---|---------------|---------------|--------------|--------------------|
| Refrigerant Type  |            | Category III: R-12, R-134a, R-401C, R-500, R-1234YF<br>Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-454B, R-502, R-509<br>Category V: R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-507 |               |               |              |                    |
| Power Supply  | V/Hz       | 115V/60Hz   |               |               |              |                    |
| Motor   | HP         | 1   |               |               |              |                    |
| Max Current Draw  | А          | 12  |               |               |              |                    |
| Compressor  |            | Oil-less, Air-cooled, Piston style  |               |               |              |                    |
| Automatic Safety Shut-Off   |            | 558 psi/38.5 bar  |               |               |              |                    |
| UL Verified<br>Recovery Rate  |            |   | R-410A        | R-22          | R-134a       |                    |
|   | lbs/min    | Direct Vapor  | 0.75 (0.34) 🕍 | 0.64 (0.29) 🖄 | 0.57 (0.26)  | 🖆 Industry Fastest |
|   | (kg / min) | Direct Liquid   | 14.44 (6.55)  | 11.11 (5.04)  | 7.85 (3.56)  |                    |
|   |            | Push/Pull Liquid  | 18.41 (8.35)  | 17.04 (7.73)  | 12.81 (5.81) |                    |
| Dimension   |            | 14.5×9.9×11.7   |               |               |              |                    |
| Weight  | lbs        | 24.3  |               |               |              |                    |
| 3-YEAR WARRANTY * NAVAC offers a 2-year over-the-counter warranty, which can extend to 3 years with registration on <u>navacglobal.com/product-registration</u> within 30 days of purchase. |            |   |               |               |              |                    |

www.navacglobal.com