

NR7 Recovery Unit



Compact · Light · Swift

Compact and Light

- Small & light weight, only 20.3 lbs
- Easy to store and carry

Brushless DC Motor

- Soft & easy starting
- Compact & efficient

Fast Recovery

- Twin cylinder
- Large condenser

CSA Safety Certification

- Full-tank, Overload & High Pressure protection

One Key Operation

- Easy to use

Purge Function

- Prevent mixing of various refrigerants

Oil-Free Compressor

- Suitable for all common refrigerants

A2L Compatible

Model		NR7			
Refrigerant Type		Category III: R-12, R-134a, R-1234YF, R-401C, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-502, R-509 Category V: R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-454B, R-507			
Power Supply	V/Hz	115V/60Hz			
Motor	HP	1			
Rated Current Draw	A	12.5			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi/38.5 bar			
UL Verified Recovery Rate	lbs/min (kg / min)		R-410A	R-22	R-134a
		Direct Vapor	0.54 (0.25)	0.58 (0.27)	0.47 (0.21)
		Direct Liquid	12 (5.5)	9 (4.1)	8 (3.6)
		Push/Pull Liquid	17 (7.8)	15.8 (7.2)	15 (6.8)
Dimension	in	12.2×9.4×9.6			
Weight	lbs	20.3			

1-YEAR WARRANTY