MAVAC

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

TUBING TOOLS

NTB7L BreakFree® Power Tube Bender **HVAC Tech's First-Choice Power Tube Bender**



- · Powerful for large size tubing
- · Push and hold for 90° bending
- · Automatic tube release
- · 7 sizes in one selector

· Stop any time for customized angles

3/4", 7/8" Bending Attachment Kit Packaging Dim & Wgt: 16" x 12.5" x 6.75, 11.75 lbs

PATENT PENDING

2-year warranty








BREAKIFREE



NEF6LM BreakFree® Power Flaring Tool Quick Accurate Flaring · Ultra Light







- · Complete a flare in 15 seconds
- · Over 100 flares per charge
- · Ultra light at 2.9 lbs
- Quick connect with ready-to-use clamps Packaging Dim & Wgt: 11.8" x 12.6" x 4.7", 9 lbs

· 45° flaring for R410A

· Large lithium battery,

over 100 bends per charge

· Quick connect mandrel and crossbar

· Tube OD: 1/4", 5/16" 3/8", 1/2", 5/8",

2-year warranty

- · Limit baffle assures precise flare depth
- · Easy one-button operation
- · Tube OD: 1/4", 3/8", 1/2", 5/8", 3/4"



Case Qty: 5

NTE11L BreakFree® Power Tube Expander

Effortless, Quick & Accurate Expanding





- · One-button operation
- · Automatic pressure relief
- · Quick connect heads
- · Large capacity lithium battery,
- up to 200 expansions per charge · Quick charge in 30 minutes
- NTEQHK Quick Connect

· Battery indicator & LED flash light

2-year warranty

/ 1-year warranty

/ 1-year warranty

- · Complete an expansion in 12 sec.
- · Battery indicator & LED flash light
- Tube OD: 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8"

BREAKIFREE

Case Qty: 4

Case Qty: 5





NTB7 Ratcheting Tube Bender

Compact · Rel



NTBRK Reverse

• 7 sizes in one selector

Bending Attachment Kit Packaging Dim & Wat: 15.2" x 9.8" x 3", 7.4 lbs

· Single crossbar for all sizes • 90° bending angle marks

- · Smooth sweep bends with no kinking

· Quick connect mandrels

- · 7 sizes in one selector
- · Ergonomic handle design

PATENT PENDING

- · Light and compact design
- Tube OD: 1/4", 5/16" 3/8", 1/2", 5/8", 3/4", 7/8"

· Patented annular rivet connection

· Internal clutch prevents over-torquing

· Reverse bending structure available

NTBRK

Case Qty: 5

NTF66 & NTF66C Flaring Tool



- · Axial spacing ensures accurate and consistent flaring
- · Eccentric cone with 45° flare for R410A system
- · Nitride treatment for longer service life
- · Robust and durable
- Packaging Dim & Wgt: 10.4" x 9.4" x 2.5", 4.7 lbs (NTF66), 4.9 lbs (NTF66C)
- Tube OD: 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"
- NTF66C with NTC12 cutter · NTF66 no cutter









NTF67D Hand or Drill-Powered Flaring Tool



- · Efficient and labor-saving with drill attached
- · Axial spacing ensures accurate and consistent flaring · Eccentric cone with 45° flare
- for R410A system · Nitride treatment for longer service life

/ 1-year warranty / · Robust and durable

Case Qtv: 5

- · Patented annular rivet connection
- · Internal clutch prevents overtorquing
- · Tube OD: 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"
- Packaging Dim & Wgt: 13.4" x 9.4" x 2.6", 2.7 lbs



NAVAC Inc.

NAVAC® Inc.

Tel/Fax: +1 877 MY-NAVAC

Info@NavacGlobal.com

www.NavacGlobal.com

Lyndhurst, NJ 07071

1099 Wall Street West, Suite 179

877 696 2822

1099 Wall St W, Suite 179, Lyndhurst, NJ 07071 P/F 877-MyNAVAC or 877-696-2822 Info@NavacGlobal.com

Page 1 of 11

www.NavacGlobal.com



Leading Technology · Superior Quality · Best Experience

Cast Qty: 10

MAVAC

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

TUBING TOOLS

NTE7 Tube Expander Easy to Expand



· Foldable design for portability

 Simple structure for expanding copper tubing

Packaging Dim & Wgt: 12"x 4.9" x 1", 0.9 lbs

· Vacuum sealed hydraulic system,

/ 1-year warranty /

2-year warranty

/ 1-year warranty /

· Easy to use

· Tube OD: 3/8", 1/2", 5/8", 3/4", 7/8"



NTE11H2 Hydraulic Tube Expander

Effortless and Durable



in



NTEQHK Quick Connect

· Easy expansion with extended lever Suitable for large diameter copper • Tube released at final trigger compression • Tube OD: 3/8", 1/2", 5/8", 3/4", 7/8",

Built-in manual relief button

no oil change needed

Expander Kit, 1-1/4" to 1-5/8" OD Packaging Dim & Wgt: 12.2"x 11" x 3.2", 6.6 lbs

· Easy one-hand operation

· Convenient for narrow spaces · Quarter-turn head design,

quick to attach/remove

• NTC6 tube OD: 1/8"~3/4"

· NTC12 tube OD: 1/8"~1-1/4"

· NTC15 tube OD: 1/8"~1-5/8"

1", 1-1/8"

NTE11H2

Case Qty: 4

NTEQHK

NTC6, NTC12, NTC15 Tube Cutter

Easy to Cut



NTC12/15

· Sharp and durable cutting blade

· Ball bearing, easy to cut and better quality

· Aluminum alloy body

· Light weight, easy to carry and use

Packaging Dim & Wgt: 3.6" x 5.1" x 1.4", 0.4 lbs (NTC6) Packaging Dim & Wgt: 9" x 5." x 1.5",0.9 lbs (NTC12) Packaging Dim & Wgt: 9" x 5." x 1.5", 1.2 lbs (NTC15)

1-year warranty

Case Qty: 6

Digital Readout · Adjustable Jaw Accurate within 2%



NTW1 Digital Torque Wrench

· Dual direction (CW &CCW)

· Torque setting memory & Peak hold

Selectable measuring units (ft-lb, in-lb, N-m, kg-cm)

Packaging Dim & Wgt: 19" x 5.7" x 3.3", 3 lbs

· Auto turn-off after 5 minutes

Case Qty (NTC6/12): 10

Case Qty (NTC15): 5

· Indicator lights and sound

NTWH41 Wrench Head Large 5-41mm For NTW1

NTWR38 Ratchet Head 3/8" Round For NTW1

for target torques

/ 1-year warranty

Dim & Wat: 9"x 4" x 1.25", 0.34 lbs

/ 1-year warranty Case Qtv: 5

NTR14 Internal & External Reamer Fast, Easy and Clean



NTD28 Tube Deburring Tool

Dim & Wat: 9"x 4" x 1.25", 0.9 lbs

· Multi-blade alloy steel internal surface

> Easy to clean internal and external tubing surfaces

Packaging Dim & Wgt: 2.1"x 2.1" x 2.6", 0.4 lbs

· Slip-resistant aluminum body · Light weight at 0.4 lbs

• Tube OD: 1/8"~1-1/2"

1-year warranty

· Replaceable blades · 2 spare blades included

Easy to carry

Packaging Dim & Wgt: 8.6"x 3.9" x 0.7", 0.1 lbs



Case Qty: 10

NAVAC Inc.

1099 Wall St W, Suite 179, Lyndhurst, NJ 07071 P/F 877-MyNAVAC or 877-696-2822 Info@NavacGlobal.com

Page 2 of 11

www.NavacGlobal.com

TUBING TOOLS

NKS2 Mini-Split Tool Kit

NAVAC Advanced Tool Kit for Mini-Split Installation



The kit includes 9 essential tools & 1 carry bag:

- NEF6LM Cordless Flaring Tool NTW1 Digital Torque Wrench
- · NVR1 Valve Core Removal Tool
- · NHK1 30-Piece Hex Wrench Set
- · NTC6 1/8"~3/4" Tube cutter
- · NTC12 1/8"~1-1/4" Tube Cutter
- · NTR14 Internal & External Reamer
- · NTD28 Tube Deburrer · NFG1 Flare Gauge

Packaging Dim & Wgt: 21" x 10" x 11", 20 lbs



NTK1 Tubing Tool Kit

Technicians' Favorite NAVAC Tubing Tools



- · Includes 5 of NTE7 tube expander, 5 of NTR14 internal/external reamer. 5 of NTC12 tube cutter, 4 of NTC6 tube cutter and one display cartons
- Counter displayable · Convenient showcase
- Easy to refill



NBF2 Lithium Battery for NEF6LM/NTE11L/NTB7L



NFG1 Flare Gauge

Dim & Wgt: 4"x 5.3" x 3", 0.3 lbs



7.2V, 2.0Ah, 14.4Wh

Kit Dim & Wat: 29.5"x 17 x 1.5", 4 lbs

Input: 120VAC/60Hz, 0.45A Output: 8.3V == 3.5A

1-year warranty

Dim & Wat: 5.5" x 5.5" x 2", 0.5 lbs

NCF2 Charger of the NBF2 Battery, for NEF6LM/NTE11L/NTB7L



· A2L compatible

· Brushless DC motor

various refrigerants

· Purge function prevents mixing of

· For precise measurement of tube flare · Tube OD: 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"

Cast Qty: 10

REFRIGERANT RECOVERY

NR7 Recovery Unit Compact · Light · Swift



NRDD Digital DC Recovery Unit

Fastest Twin-Cylinder Recovery Unit

DEALER DESIGN

AWARDS

· Small & light weight at only 20.3 lbs

Packaging Dim & Wgt: 5.1"x 1.6" x 0.2", 0.14 lbs

- · Easy to store and carry
- · One key operation, easy to use
- · Twin cylinder, fast recovery · Oil-free compressor, suitable for

· Brushless DC technology

Twin-cylinder with 2-row oversized


condenser for fast recovery

· Light weight at 24.3 lbs

· Large backlit display · Easy-to-read LCD screen

all commonly used refrigerants


Packaging Dim & Wgt: 12.2" x 9.4" x 9.6", 20.3 lbs



1-year warranty







*2 years over-the-counter warranty extended to 3 years by registering on NAVAC website

· Oil-free compressor, suitable for



Compatible

Compatible



Leading Technology · Superior Quality · Best Experience

NRDDF Recovery Unit for Flammable Refrigerants

Fast · Compact · Ignition-Proof



- · Designed and tested to UL 121201,CSA C22.2 No.213-17 & IEC 60069-7
- · Suitable for A2L, A2 & A3 refrigerants · Brushless DC technology
- · Oil-free compressor, suitable for all commonly used refrigerants
- · Easy-to-read LCD screen Packaging Dim & Wgt: 18" x 12.8" x 11.3", 26 lbs

· IP54 waterproof design

- · Large backlit display
- · Twin-cylinder with 2-row oversized condenser for fast recovery
- Purge function prevents mixing of various refrigerants

from sealed HVAC/R systems

· Easy-to-read LCD screen





NRDC4M 4-Cylinder Recovery Unit Fastest • Most Powerful



- · Up to 40% faster than 2-cylinder unit
- · Super-efficient condenser
- · Over-sized micro-channel coil
- Packaging Dim & Wgt: 17.5" x 14" x 11", 45 lbs

· 4-cylinder for powerful recovery

- · Brushless DC technology · Large backlit display
- · Dual oil-free compressor, suitable DEALER DESIGN • 3 high-speed cooling fans for all commonly used refrigerants

/*1-year warranty

AZL Compatible

MASTER SERIES



VACUUM PUMPS

NP2DLM BreakFree® Cordless Vacuum Pump Cordless · Compact · Convenient



DEALER DESIGN

- · 2 CFM, 23 microns
- · High performance lithium battery
- · Up to 1 hour running time
- · Brushless DC technology
- · Light weight at 8.4 lbs

Packaging Dim & Wgt: 15.2" x 8.9" x 9.4", 14.5 lbs

- · Compact design
- · Dual-stage
- · Backflow prevention check valve
- Isolation valve
- · 1/4" & 3/8" inlet

2-year warranty

BREAKIFREE



BREAKIFREE

⊂omoatible



NP4DLM BreakFree® Cordless Vacuum Pump

Cordless · Compact · Convenient



- · 4 CFM, 15 microns
 - · Residential and light commercial applications
 - · High performance lithium battery
 - Up to 1 hour running time
 - · Brushless DC technology Packaging Dim & Wgt: 14.2" x 8.9" x 10.9", 20 lbs

2-year warranty

- · Compact design, light weight at 15.4 lbs
- · Dual-stage pump with gas ballast · Backflow prevention check valve
- · Isolation valve & Lifting hook
- · 1/4", 3/8" & 1/2" inlet



NB1 Lithium Battery for NP2DLM



Dim & Wgt: 3.1"x 2.8" x 4.8", 1.3 lbs

18V. 9Ah. 162Wh





Dim & Wgt: 3.5"x 3.1" x 4.8", 2.0 lbs

NBP2 Lithium Battery for NP2DLM/NP4DLM



NAPS1 Power Supply Adapter for NP2DLM/NP4DLM Input: 100-240V~50/60Hz, 4.5A, 450VA Output: 21V, 20A





Dim & Wgt: 12.2"x 6.3" x 3", 4.4 lbs

NP5DP & NP7DP Vacuum Pump



1099 Wall St W, Suite 179, Lyndhurst, NJ 07071

P/F 877-MvNAVAC or 877-696-2822


Info@NavacGlobal.com

· NP5DP: 5 CFM, 15 microns

- NP7DP: 7 CFM, 15 microns, dual
- and reliability

- Dual-stage with integrated cylinder structure for high performance
- Packaging Dim & Wgt: 16.7" x8. 5" x 13.6", 32 lbs 1/4", 3/8" & 1/2" inlet

/ 1-year warranty



backflow · Forced oil circulation for efficiency

- and durability
- · Gas ballast · Lifting hook

PROSERIES



MAVAC

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

VACUUM PUMPS

NP7DPF Vacuum Pump for Flammable Refrigerants

NRP6Di & NRP8Di Smart Vacuum Pump

Brushless DC Technology with Smart Control

NP7DP2 Vacuum Pump Performance · Reliabilit



- 7 CFM, 15 microns
- · Dual-stage with integrated cylinder structure for high performance and reliability
- · Internal check valve to prevent oil backflow

Unit Dim & Wgt: 14" x 5" x 11.3", 26 lbs

· Designed and tested to UL 121201, CSA C22.2 No. 213-17 and IEC 60079-7 Standards

- Suitable for A2L, A2 and A3 refrigerants
- · Prevent oil backflow Unit Dim & Wgt: 14" x 5" x 11.3", 26 lbs

· NRP6Di: 6 CFM, 15 microns

· NRP8Di: 8 CFM, 15 microns

· Automatic control, digital display

Unit Dim & Wgt: 14" x 5.3" x 11.9", 25.4 lbs

· Brushless DC technology

Light weight at 25.35 lbs

with task reminder

· 12 CFM, 5 microns

· Industrial-grade design

· High evacuation performance

· Brushless DC technology

· Oil backflow prevention

· Integrated dual-stage pump

Unit Dim & Wgt: 16.3" x 6" x 12.1", 32 lbs

· Forced oil circulation for efficiency

· Forced oil circulation for efficiency

· A2L compatible

and durability

Gas ballast

· Lifting hook

· 1/4", 3/8" & 1/2" inlet

1-year warranty

2-year warranty

· Safe & convenient for rooftop use

· Built-in micron vacuum gauge for

· Solenoid valve for vacuum preser-

vation and oil backflow prevention

· Dual-stage pump with gas ballast

- and durability
- · Gas ballast
- Lifting hook
- · 1/4". 3/8" & 1/2" inlet

easy leak detection

· 1/4", 3/8" & 1/2" inlet









- · Ball drain valve, easier to drain oil · Large oil sight glass for better view
- · Adjustable gas ballast
- · 1/4", 3/8" & 1/2" inlet

MASTER SERIES





NP12DA1 Ammonia Vacuum Pump



NRD16T Industrial Vacuum Pump

Suitable for Heavy Commercial Applications

NP12DM Vacuum Pump

Fast · Robust · Powerful

- · Corrosion resistant for Ammonia (R-717)
- · 12 CFM. 5 microns
- · Industrial-grade design
- Brushless DC technology
- Integrated dual-stage pump

Unit Dim & Wgt: 16.3" x 6" x 12.1", 32 lbs



- · 12 CFM, 3 microns
- · Industry-leading ultimate vacuum
- · Fast evacuation with power and
- Oil backflow prevention Unit Dim & Wat: 20.5" x 7.4" x 10.7", 73 lbs

1-year warranty

- · Oil backflow prevention
- · Ball drain valve, easier to drain oil
- · Large oil sight glass for better view
- · Adjustable gas ballast
- · Inlet/Exhaust: KF25







· Integrated cylinder structure

- · Forced oil circulation
- · Adjustable gas ballast Inlet: Kf16
- Exhaust: KF25



P/F 877-MyNAVAC or 877-696-2822 Info@NavacGlobal.com

1099 Wall St W, Suite 179, Lyndhurst, NJ 07071





Compatible



















/ 1-year warranty







www.NavacGlobal.com

Page 4 of 11

www.NavacGlobal.com



Leading Technology · Superior Quality · Best Experience

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

VACUUM PUMPS

NRD24M & NRD30M Industrial Vacuum Pump Fast · Powerful · Reliabl



- · NRD24M: 18 CFM, 3 microns
- · NRD30M: 23 CFM, 3 microns
- · Industry-leading ultimate vacuum · Fast evacuation with power and reliability
- · Oil backflow prevention
- Packaging Dim & Wgt: 29.5" x 9.8" x 17.3", 95.8 lbs

1-year warranty

- · Corrosion resistant for Ammonia
- · Integrated cylinder structure

(R-717)

- · Forced oil circulation · Adjustable gas ballast
- · Inlet/Exhaust: KF25



✓ Industrial



NVO1G (1 Liquid Gallon) • Low volatility and high resistance to oxidation Quantum Premium Vacuum Pump Oil

- NVO1Q (1 Liquid Quart) · Advanced non-misting formulation
 - Extremely pure hydro processed mineral oil
 - · Excellent lubricity & pump protection at deepest vacuum
 - · Suitable for most vacuum pumps available in the market
 - Case Qty (NVO1Q/NVO1G): 12/4





Industrial Grade

NPO68



NOT30B

Oil Mist Filter

for NRD16T/





MASTER SERIES

Packaging Dim & Wgt:

21" x 12.1" x 15.8", 41.1 lbs

NOT30B

Dim & Wgt: 9" x 3.5" x 3.5", 2.1 lbs (NVO1Q)

11.5" x 6.5" x 4.5", 7.6 lbs (NVO1G)

5.5" x 5.5" x 7.5", 3 lbs (NOT30B)

8.3" x 5" x 2". 3 lbs (NPO68)

NPO68

 6 CFM DC dual-stage vacuum pump Built-in advanced digital manifold gauge

· Wireless refrigerant scale

- · Built-in micron vacuum gauge with leak detection
- · Wireless temperature probes

NRC62D Smart Refrigerant Charging Machine Smart Charging

NVO1Q





"3-in-1" Smart Charging Machine w. Digital Manifold, Vacuum Pump and Refrigerant Scale

TESTING TOOLS & INSTRUMENTS

NVR1 Valve Core Removal Tool Fast Recovery and Evacuation



sizes in 1 tool

/ 1-year warranty /

- · For use with both 1/4" and 5/16" flare fittings
- · Designed for high-pressure refrigerants Including R410a Packaging Dim & Wgt: 5.4" x 6.2" x 1.8", 0.6 lbs • Vacuum rated to 20 microns

1-year warranty



Case Qty: 5

Case Qty: 5

NMV1 Micron Vacuum Gauge



NMV1S Premium Micron Vacuum Gauge

1099 Wall St W, Suite 179, Lyndhurst, NJ 07071

P/F 877-MvNAVAC or 877-696-2822 Info@NavacGlobal.com

· Pirani vacuum sensor, professional grade and more precise

· Large backlit display

· Auto power off

Packaging Dim & Wgt: 4.4" x 2.2" x 7.2", 1 lbs

· Pirani vacuum sensor, professional

grade and more precise

· Rechargeable battery

· Large backlit display

· Auto power off

· Buzzing alert

Vacuum level reminder

· Vacuum leakage warning

· Ergonomic design

/ 1-year warranty

· High pressure protection · Buzzing alert

· Vacuum level reminder · Vacuum leakage warning

· Ergonomic design

Packaging Dim & Wgt: 3.5" x 2.6" x 6.1", 0.8 lbs Work with MyNAVACTM APP





Case Qty: 5







TESTING TOOLS & INSTRUMENTS

NML1 Leak Detector





NMC1 Digital Clamp Meter

· Semiconductor sensor for precision

· 2 CFM ball bearing sniffing fan for detecting very small leaks

· Extended service life

High precision chip

• 1-1/8" jaw, suitable for large

· Compact design

conductors

Packaging Dim & Wgt: 12.1" x 2.9" x 10.6", 2.6 lbs

/ 1-year warranty /

Case Qty: 5

- · Rechargeable lithium battery
- · Auto power off
- · Easy to carry · Ergonomic design



/ 1-year warranty

Case Qty: 5

· Auto power off · Backlit LCD, easy to read



NMT300 Infrared Thermometer

Simple · Solid



· Precise infrared sensor

· Rapid response, accurate measurement

· Large-aperture silicon mirror for long-distance reach

Packaging Dim & Wgt: 5.7" x 1.9" x 9.7", 0.6 lbs

Packaging Dim & Wgt: 6" x 1.7" x 9.4", 0.9 lbs

/ 1-year warranty

2-year warranty

Case Qty: 6

 Wide measuring range · One-key operation

Auto power off

· Backlit LCD, easy to read



Case Qty: 12

NMT1000 Thermal Imaging Camera Troubleshoot HVAC systems through a new lens



· High-quality imaging

· Distinctive thermal vision of the target

· 25 Hz fast refresh frequency · Smooth video and measurements

· Compact design, easy to carry

· Quick temperature measurement · Covers the entire field of the target

Auto temperature range

· Quick start in 8 seconds Store and export images



Case Qty: 5

NRS2i01 Wireless Refrigerant Scale



· Wireless bluetooth control

Auto power off

· Weight range up to 220 lbs · Precision sensor with 0.05% accuracy

 Magnesium alloy weighing platform Packaging Dim & Wgt: 10" x 3.8" x 12.4", 5.7 lbs

/ 1-year warranty · Light weight at 3.3 lbs, easy to carry

· Large backlit display · Integrated handle design

· Convenient hide-away storage for handheld device



NRS3i01 Wireless Refrigerant Scale, Large Weighing Platform

Precise Charging



· Wireless bluetooth control

· Auto power off

 Weight range up to 265 lbs · Precision sensor with 0.05% accuracy

· 10.6" x 12.6" large weighing platform Packaging Dim & Wgt: 15.7" x 3.6" x 14.1", 10.4 lbs

· Durable and highly reliable · Large backlit display · Integrated handle design

· Convenient hide-away storage for handheld device

· Auto power off

Large opening

· Robust design

Case Qty: 4

NST1 & NST2 Wireless Temperature Clamps, High and Low side



· Work with MyNAVAC™ APP

· Wireless connection with Nexus Digital Manifold Gauge Digital display

Packaging Dim & Wgt: 8.2 "x1.6"x9", 0.7lbs

2-year warranty

/ 1-year warranty

Case Qty:





1099 Wall St W, Suite 179, Lyndhurst, NJ 07071 P/F 877-MyNAVAC or 877-696-2822 Info@NavacGlobal.com



Leading Technology · Superior Quality · Best Experience

MAVAC

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

Case Qtv: 5

MANIFOLD GAUGES

NX1/NX1V Nexus Digital Manifold Gauge




- NST1, NST2
- Work with MyNAVAC™ App
- · Bluetooth connections with temp clamps & micron gauge
- Modes: Manifold mode with SH/SC display, Leak Test, Evacuation & Decay

2-year warranty

/ 1-year warranty

/ 1-year warranty



- · Work with 72 commonly used refrigerants
- · 1/4 turn ball valve handles

NX1 includes temp probes

Packaging Dim & Wgt: 14.3" x 13.3" x 4,2", 6 lbs • NX1V includes NX1 and micron gauge

Case Qty: 5





N2D72 Flex72 Manifold Gauge with Digital Display







N2D4H Manifold Gauge with Digital Display

Impact-Resistar

- · Precise pressure gauge with Class 0.4 accuracy
- · Aluminum body with ball valve handle

· Aluminum body with ball valve handle

- · Impact-resistant design
- Durable rubber cover

Class 0.4 accuracy

· Impact-resistant design

· Durable rubber cover

Packaging Dim & Wgt: 11.8" x 12.5" x 3.3", 5.4 lbs • 1/4 turn ball valve handles

· Precise pressure gauge with

2-year warranty Case Qty: 5



· Hidden hook design, easy to transport · Auto power off



Work with 72 commonly used refrigerants

· Easy-to-read digital display


Case Qty: 5



Compatible



at a glance



· Hidden hook design, easy to transport



· Illuminating, glow in the dark

· NMG11A: R410A/22/134a/404A

NMG12A: R454B/32/410A/22



Case Qtv: 5

PROSERIES

NMG12A/13A: AZL

NMG11A/12A/13A/14A/15A Pro Manifold Gauge

Simple · Reliable



Precision · Impact-Resistant

· Reliable brass body w. needle valve

- · Precise pressure gauge with Class 1.0 accuracy
- · Reliable, efficient and durable
- Ø3-1/8" large dial for easy reading
- Packaging Dim & Wgt: 9.2" x 8.8" x 1.8", 2.3 lbs NMG15A: 4E: R134a/404A/410A

· NMG13A: R32/454B/22 · NMG14A: R22/410A/404A

N2A4 & N2A4B/C/D/E Pro Plus Manifold Gauge

- · Precise pressure gauge with Class 1.0 accuracy
- · Aluminum body w. 1/4 turn ball valve
- · Impact-resistant design
- Ø3-1/8" large dial for easy reading
- N2A4B: R454B/32/410A/22N2A4B/C: N2A4C: R32/454B/22
- · N2A4D: R22/410A/404A Packaging Dim & Wgt: 13.8" x 13.4" x 4", 5.5 lbs • N2A4E: R134a/404A/410A

Case Qty: 5 / 1-year warranty · Illuminating, glow in the dark · N2A4: R410A/22/134a/404A



Case Qty: 5





N2A4C/D/E

N4A4 & N4A4B Pro Plus 4-Valve Manifold Gauge N4A4H Pro Plus 4-Valve Manifold Gauge with Hoses



· 4 valve, easy-to-use

- · Precise pressure gauge with Class 1.0 accuracy
- 4 Refrigerants for wider applications
- Aluminum body with 1/4 turn ball valve
 N4A4B: R454B/32/410A/22
- Ø3-1/8" large dial for easy reading Packaging Dim & Wgt: 12.1" x 13.5" x 4", 6.5 lbs (N4A4(B)), 9.5 lbs (N4A4H)

1-year warranty



- · 4-color refrigerant hoses included
- · N4A4 & N4A4H: R410A/22/134a/404A
- N4A4H includes 4-color 5' refrigerant hoses

N4A4B: AZL N4A4(B)



NMH11~15H Manifold Head, High Side



P/F 877-MvNAVAC or 877-696-2822

Info@NavacGlobal.com

1099 Wall St W, Suite 179, Lyndhurst, NJ 07071



NMGB1 Impact-Resistant Rubber Boots, Set of 2









NMH11~15L Manifold Head, Low Side





HOSES & HOSE KIT

NH5S 1/4" Charging Hoses w/o Ball Valve, 5 Ft Long NH5SC 1/4" Charging Hoses with Ball Valve, 5 Ft Long



- High strength
- · Ball valve to prevent refrigerant loss
- · Suitable for R-410A, R-134a, R-22 and other refrigerants
- 1/4" SAE fittings with 45° bend Packaging Dim & Wgt: 10.1" x 10" x 2", 2 lbs

/ 1-year warranty

- · Leak-proof eight-sided crimp
- · 800 psi working pressure, 4000 psi burst pressure
- · Metal valve handle
- · Universal, replaceable gasket



NH5R, NH5B, NH5Y Individual Charging Hose w/o Ball Valve



- High strength
- · Ball valve to prevent refrigerant loss
- Suitable for A2L reversed thread refrigerant & recovery tanks
- 1/4" SAE fittings with 45° bend

/ 1-year warranty

/ 1-year warranty

- · Leak-proof eight-sided crimp
- · 800 psi working pressure, 4000 psi burst pressure
- · Universal, replaceable gasket

· Leak-proof eight-sided crimp

psi burst pressure

· Metal valve handle

· 800 psi working pressure, 4000



Case Qty: 5

Case Qty: 5

Compatible

Case Qty: 5

NH5CB, NH5CR, NH5CY Individual Charging Hose with Ball Valve



- High strength
- · Ball valve to prevent refrigerant loss
- Suitable for A2L reversed thread refrigerant & recovery tanks
- 1/4" SAE fittings with 45° bend Packaging Dim & Wgt: 10.8" x 9.4" x 2.1", 1.3 lbs

· Ball valve to prevent refrigerant loss

Suitable for A2L reversed thread

refrigerant & recovery tanks

· 1/4" SAE fittings with 45° bend

· Universal, replaceable gasket



· 800 psi working pressure, 4000 psi burst pressure

NH38BB: 3/8" to 3/8" fitting

Universal, replaceable gasket

Packaging Dim & Wgt: 10.8" x 9.4" x 2.1", 1.3 lbs



NH38BB Big Boy Evacuation Hoses, 5 Ft long

NH5L 1/4" Refrigerant Hose, A2L Reversed Thread



· High strength

High strength

- · 3/8" large diameter for fast evacuation
- 4-layer construction for low permeation · 460 psi working pressure, 2300 psi burst
- pressure

Packaging Dim & Wgt: 12.9" x 11.1" x 2.2", 1.4 lbs

NHR38AA & NHR38AB Big Boy Recovery Hoses, 6 Ft long

· High strength

- 3/8" large diameter for fast recovery
- · 4-layer construction for low permeation · 460 psi working pressure, 2300 psi burst
- Packaging Dim & Wgt: 12.9" x 11.1" x 2.2", 1.4 lbs

· Heavy-duty gaskets with extras included

· Heavy-duty gaskets with extras included

- · NHR38AA: 1/4" to 1/4" fitting · NHR38AB: 1/4" to 3/8" fitting



Case Qty: 5

Case Qty: 5

NHB1 & NHB2 Big Boy High-Flow Hoses, 6 Ft long



· High strength

pressure

- 1/2" large diameter for fast evacuation
- 4-layer construction for low permeation · 640 psi working pressure, 3200 psi burst
- Vacuum rated to 20 microns

/ 1-year warranty

• NHB1: 1/4" to 3/8" fitting · NHB2: 1/4" to 1/2" fitting

Page 9 of 10

Packaging Dim & Wgt: 14.5" x 13.4" x 2.5", 2 lbs

· Heavy-duty gaskets with extras included



1099 Wall St W, Suite 179, Lyndhurst, NJ 07071 P/F 877-MyNAVAC or 877-696-2822 Info@NavacGlobal.com



Leading Technology · Superior Quality · Best Experience

MAVAC

Brightness in Your Palm

Empowering You to Work Smarter

Leading Technology · Superior Quality · Best Experience

HOSES & HOSE KIT

NH34AB & NH34AC Big Boy High-Flow Evacuation Hoses, 3 Ft long



· High strength

- 3/4" large diameter for fast evacuation
- · Premium material for durability and flexibility
- Vacuum rated to 20 microns

Packaging Dim & Wgt: 14.5" x 13.4" x 2.5", 1.8 lbs

/ 1-year warranty /

/ 1-year warranty

- · Heavy-duty gaskets with extras included
- NH34AB: 1/4" to 3/8" fitting
- NH34AC: 1/4" to 1/2" fitting



Case Qty: 5

NEVK1, NEVK2 Rapid Evacuation Kit, Pro Series NEVK3, NEVK4 Rapid Evacuation Kit, Pro Plus

NEVK1 includes:

1 x NHB1 Evacuation Hose, 3/8" to 1/4" Fitting 1 x NHB1 Evacuation Hose, 3/8" to 1/4" 1 x NVR1 Valve Core Removal Tool

NEVK2 includes:

1 x NHB2 Evacuation Hose, 1/2" to 1/4" Fitting 1 x NVR1 Valve Core Removal Tool

1 x NHB1, 1 x NHB2, 2 x NVR1 1 x NMV1 Micron Vacuum Gauge

NEVK4 includes:

- 1 x NHB2 Evacuation Hose. 1/2" to 1/4"
- 1 x NVR1 Valve Core Removal Tool





NEVK1&2

Case Qty (NEVK1/2/3/4): 5/5/4/4



NEVK3 includes:

2" x 1.9" x 13.5", 3.3 lbs (NEVK1/2) 10.6" x 5.9" x 11", 6.9 lbs (NEVK3) 10.6" x 5.9" x 11", 3.9 lbs (NEVK4)

Packaging Dim & Wgt:

FITTINGS

F1028 & F1029 Rapid Y Connection Fitting

No Assembly · Less Turbulence · More Flow



- · Single-piece solid brass construction
- · Vacuum rated to 20 microns
- · Large internal boring for maximum flow and minimal resistance

Packaging Dim & Wgt: 5.7"x 3.1" x 1.5", 0.63 lbs

/ 1-year warranty

/ 1-year warranty



Case Qty: 5

- · F1028 2 x 3/8" MPT to 1x 3/8" FPT
- · F1029 2 x 3/8" MPT to 1x 1/4" FPT



Case Qty: 5

FHH4 4 Port Hose Holder



· Supporting professional hose management · Light weight at 0.15 lbs

1-year warranty

- · Holding multiple hoses
- · Premium metal material, built to last
- · Modern finish for sleek aesthetic

Packaging Dim & Wgt: 5.7" x 3.1" x 1.5", 0.23 lbs

· Suitable for multi-sized fittings



· 1/4", 1/4", 3/8", 1/2"



F2010

A2L Adaptor for LH A2L Refrigerant Tanks F2010 1/4" LH FPT x 1/4" MPT





Case Qty: 5

Dim & Wgt: 5.70x3.10x1.50, 0.13 lbs

NF43

Premium Oil Mist Filter For NP12DM. NP12DA1(for non-ammonia applications)






Dim & Wgt: 4.52x4.52x4.92, 1.17 lbs

PERSONAL & LIFESTYLE PRODUCTS

Case Qty: 10 / 1-year warranty /



· Convenience and Portability, 2-way clip

· Rechargeable Battery, Up to 2 hours runtime

Page 11 of 11



Dim & Wgt: 4.92x7.09x1.50, 0.18 lbs

brightness

· Extra-bright at 300 lumens

PL2 Headlamp

Versatile Way to Light Your Path



- · Extra-bright at 350 lumens
- · Long-distance illumination up to 330 feet

· Long-distance illumination up to 330 feet

· Adjustable lighting for customized

- 5 Lighting Modes: High (COB), Low (COB), High (Spot), Low (Spot), Strobe
- · COB LED with Latest Technology

Dim & Wgt: 7.48x5.51x1.38, 0.22 lbs

/ 1-year warranty

Case Qty: 10

· Comfortable Headband, Breathable and stretchable material

· Rechargeable Battery, Up to 6 hours runtime

