



Empowering you to work smarter



Compatible with *myNAVAC™* App

# NSV1 Smart Refrigerant Valve



**A2L  
Compatible**



## Smart Refrigerant Flow Control

### Precision Task Management

- Automatic charging & recovery
- Fast, low-latency operation

### Bluetooth Connectivity

- Works wirelessly with myNAVAC™ App and NRS2A refrigerant scale

### Smart Operation Solenoid Valve

- Status Indicator for Flow, Bluetooth Connection, and Power

### Rechargeable Lithium Battery

- Up to 60 hours battery life
- Battery indicator

### Durability and Convenience

- Impact resistant design, IP54 rating
- Compact design with folding hook

Model	NSV1
Maximum Working Pressure	551 psi (38bar)
Ports	1/12" (2 mm)
Operating Environment	14~122°F (-10~50°C)
Storage Temperature	14~122°F (-10~50°C)
Power Supply	Rechargeable 1000mAh Lithium Battery, Type-C Charging Port
Rechargeable Battery Operating Time	60 hours
Bluetooth Range	>98.4' (30m)
Dimensions	4.76"H x 3.62"W x 1.87"D (121 x 92 x 48 mm)
Unit Weight	1.33 lbs
Accessory	Carry bag

**1-YEAR WARRANTY**

www.navacglobal.com