

SK2TP1 SK3TPH1 SK4TPHM1 Smart Probe Kit



SK2TP1
Smart Refrigerant Diagnostics Kit



SK3TPH1
Smart Refrigerant & Air Side Diagnostics Kit



SK4TPHM1
Smart Refrigerant & Air Side Diagnostics Pro Kit

Smart Charging & Comfort Diagnostics

Smart Probes with Digital Display

- Probes are suitable for standalone use
- Works wirelessly with myNAVAC™ App
- High accuracy sensors
- Built-in digital screen

NSH1 Bluetooth Psychrometers

- Detailed psychrometric datapoints
- Rechargeable lithium battery & built-in magnet
- Easy-to-switch knob, suitable for either Side Supply (SP) or Return (RT)

NST1 NST2 Bluetooth Temperature Clamps

- 1-5/8" opening
- High accuracy thermistor sensor
- Bluetooth connection with NEXUS Digital Manifold Gauge

NSM1 Bluetooth Psychrometers

- Tip direction indicator
- Rechargeable lithium battery & built-in magnet
- Easy-to-switch knob, suitable for multiple measuring points

NSP1 Bluetooth Pressure Probes

- Auto VSAT / LSAT calculations thru App
- Rechargeable lithium battery
- Easy-to-Switch Knob, suitable for either High (HP) or Low (LP) Side

Save Money & Space

- Compact carry bag
- Includes (2) 1/4" SAE Access Tee

Model	NST1 (Low Side)/NST2 (High Side)	NSP1	NSH1	NSM1
Description	Bluetooth Temperature Clamp	Bluetooth Pressure Probe	Bluetooth Psychrometer	Bluetooth Manometer
Measuring Range	-40~257°F (-40~125°C)	-29~725 psi (-1~50 bar)	Humidity: 0~100% RH / Temp: -40~249.8°F	-8~64 inWC
Accuracy	± 2.3°F (± 1.3°C)	± 0.5%	Humidity: ±2.0%RH (10 to 90%RH) (at 77°F) ±5.0%RH (<10%RH or >90%RH) (at 77°F) Temperature: ±1.1°F (-4°F~32°F) ±0.9°F (32°F~140°F) ±1.3°F (140°F~248°F)	±0.02 inWC on 0.00~±2.00 inWC (±1.5% FS on ±2.00~±60.00 inWC)
Resolution	0.1°F	0.01 psi	0.1%RH, 0.1°F	0.01 psi
Battery Type	2 x AAA	Rechargeable Lithium Battery	Rechargeable Lithium Battery	Rechargeable Lithium Battery
Bluetooth Range	450 ft (150m) line of sight	164 ft (50m) line of sight	164 ft (50m) line of sight	164 ft (50m) line of sight
Unit Weight	5.6 oz	7.8 oz	7.8 oz	7.6 oz

1-YEAR WARRANTY